

Socket Pipe Plugs 7/8 Taper

*(Dimensions are for reference ONLY!)
(There are many different plug standards, Short, Long and can vary by Material)*

Socket Pipe Plug 7/8 Taper							
Flush Seal							
Alloy Steel (38 HRC) = PPS73800---- Stainless Steel = PPS7188---- Stainless Steel = PPS7316---- Nylon = PPS7NYL----							
Nominal Size	O	Threads Per Inch	S	K	W	L	
	Nominal O.D.		Hex Socket Size	Key Engagement	Wall Thickness	Max	Max
				Min	Min		
1/16	0.307	27	5/32	.140	.052	.250	.235
1/8	0.401	27	3/16	.140	.049	.250	.235
1/4	0.529	18	1/4	.218	.045	.406	.391
3/8	0.667	18	5/16	.250	.040	.406	.391
1/2	0.830	14	3/8	.312	.067	.531	.516
3/4	1.041	14	9/16	.312	.054	.531	.516
1	1.302	11-1/2	5/8	.360	.112	.656	.641
1-1/4	1.647	11-1/2	3/4	.360	.102	.656	.641
1-1/2	1.885	11-1/2	3/4	.360	.102	.656	.641
2	2.360	11-1/2	1	.360	.102	.656	.641
2-1/2	2.854	8	1	.500	.250	1.015	.995
3	3.480	8	1	.500	.250	1.015	.995
3-1/2	3.980	8	1	.500	.250	1.015	.995
4	4.479	8	1	.500	.250	1.015	.995

Note: "3/4 Taper" and "7/8 Taper" fit into the same hole. The "3/4 Taper" will stick up out of the hole a bit, the "7/8 Taper" will be Flush.
 Note: Both "3/4 Taper" and "7/8 Taper" can be referred to as "Dry Seal".

Actual Outside Diameters of Pipe Thread					
(Dimensions are same for all types of plugs)					
1/8-27	1/4-18	3/8-18	1/2-14	3/4-14	1-11 1/2